




COVERAGE
2,5 L = ± 4m²

DRYING TIME
24h before paint



STRIPS

Glue in a single application

Format : 2,5 L

EASY, FAST, EFFICIENT!

- Removes all types of glue used on flexible flooring including neoprene glues: glues used for carpet, vinyl floors, plastic floors, sisal and seagrass, etc
- Can be applied to all types of flooring: wood, concrete, tiling, marble, glass, metal, etc
- Non-drip on vertical surfaces
- Glue waste does not stick to tools

Preparation Glue stripper



STEPS FOR A SUCCESSFUL PROJECT

The coverage rate is given for information purposes only. It will vary depending on the type of surface, and the type, thickness and quantity of glue residue

For large areas of flooring, work in roughly 1m² sections

Do not allow the stripper to come into contact with painted or varnished surfaces, or any plastic or textile materials.

> STEP 1 - PREPARATION

Remove the floor covering

Using a large utility knife, cut out narrow strips from the floor covering.

Once cut out, use them as handles to pull the entire floor covering away. If still difficult to remove: wear protective clothing and pour the stripper onto a corner of the covering. Leave for a few minutes. Pull back then unstick the covering using a pallet knife.

Scrape off the glue

Using a scraper or wide pallet knife, scrape off as much of the glue residue stuck to the floor as possible.

Remove the waste

Do not forget to vacuum the dust.

If you want to paint the floor at a later stage, be careful not to dig into the surface when scraping off the glue.

> STEP 2 - APPLICATION

TOOLS

Paintbrush, pallet knife, protective gloves and glasses. Wear protective gloves and glasses.

Shake the container before use.

1. Liberally spread the stripper over any glue residue using a paintbrush. The coat applied should be the same thickness as the glue residue.
2. Leave for approx. 1 hour depending on the type of glue and its thickness. For neoprene glue, leave for at least 1 hour.
3. Scrape off the softened glue residue using a pallet knife.
4. Repeat until all the glue has been removed.
5. Use warm water and a stiff brush (nylon or scrubbing brush) to rinse off the stripped surface. Rinsing the surface is not necessary if the glue has been scraped off carefully.
6. Leave to dry for 24 hours.

7. Then apply Renovation paint*:

> V33 Tiled Floor & Stair Renovation paint for tiled or marble flooring

> V33 Wooden Floor & Stair Renovation paint for wood or laminate flooring

- Test on a small area first
- On wood, use the pallet knife in the direction of the grain
- Do not apply the stripper in direct sunlight, do not store in a warm place and ensure the room is well ventilated when in use
- Clean tools in water
- If splashed onto a painted, varnished, textile or plastic surface, wipe immediately with a damp cloth or sponge.

*Before applying paint:

> If necessary, sand, smooth or fill any holes or irregularities in the floor.

> Make sure that all traces of glue have been completely removed from the surface.

> Wait for the floor to dry out fully, i.e. at least 24 hours.