



ASPECT
Satin

COVERAGE
750 ml = ± 10 m²
2 L = ± 24 m²

DRYING TIME
RECOAT
12 hours


FULLY DRY
24 hours



Formats : 750 ml – 2L

EASY, FAST, EFFICIENT!

- Stain resistant: hot and cold fat, vinegar, wine, tomato sauce, coffee, tea or cosmetics
- Resistant to household products: water, washing up liquid, all-purpose cleaner, diluted bleach
- Resistant to direct impact, scratches and water splashes
- Washable with mild detergent



Renovation Cupboards & Cabinets



STEPS FOR A SUCCESSFUL PROJECT

This paint is designed for built-in kitchen cupboard doors, wall tiles and wall panels. It is not suitable for waxed or oiled surfaces, bathroom or shower tiling, or flooring.

Surface PREPARATION is ESSENTIAL. See Step 1 below.

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

> STEP 1 - PREPARATION

- VARNISHED WOOD, PAINTED WOOD and PVC : wash, rinse thoroughly with water, leave to dry, then lightly sand (240 grit) and remove dust.
- MELAMINE, LAMINATE, WALL TILES, GLASS and small items of METALWORK (brass, aluminum, galvanized, zinc) : wash and rinse thoroughly with water, leave to dry.
- RAW / POROUS SURFACES (wood, mdf) : lightly sand (240 grit) and remove dust.

WASHING the surface with a soda-based (alkaline) cleaner is essential.
Greasy or plastic-coated materials can affect the adhesion of the paint.

> STEP 2 - APPLICATION

TOOLS :

Paint mixer or wide stick • 5mm pile paint roller • Round edged paint brush (for angles, corners, joints & finishes)
Before applying, stir the paint with a mixer or wide stick, working around the bottom of the tin to mix it well.
This is a ready-to-use product, do not dilute.

1. Start by painting the corners and moldings of your first painting surface.
2. Distribute the paint evenly on your roller and apply from top to bottom. Follow with successive cross strokes (moving from left to right).
3. Finish from top to bottom for perfect results.

To obtain the optimal performance and resistance, two coats of paint are essential (Touch dry: 2 hours - Recoat: 12 hours - Fully dry: 24 hours). For bright colours, dark or porous surfaces, it may be necessary to apply an additional coat.
Interior use only • Work on small surfaces (from 0.5-1m²) • Observe the recommended coverage rate • Do not apply the product either too thickly or too thinly • Apply the paint between 12 and 25 °C and avoid draughts • Do not stop applying the product in the centre of a surface • Do not start reapplying the product while it's still drying • Remove as much paint as possible from brushes and rollers before washing. Clean your tools with water • To clean painted surfaces, use a gentle detergent. Do not use abrasive sponges.