



0.75L 2.5L

**INTERIOR PAINT**  
**FURNITURE AND WOODWORK**



**IMPACT  
AND STAIN  
RESISTANT**



**HIGHLY  
DURABLE**



**MULTI-  
SURFACE**

Easy as 1,2,3!

1  CHOOSE your project **INDOOR** OR **OUTDOOR**

2  Pick your colour

3  EXPRESS YOURSELF  
enjoy!)





#### DRYING TIME



Recoat



Fully dry

#### TOOLS



Brush



Roller

#### TOOL CLEANING



Water

#### COVERAGE

1L e

1X ± 16<sup>m2</sup>

### PREPARATION

Preparation is an ESSENTIAL stage.

- POROUS TIMBERS (unfinished timber, mdf, etc.): Sand down the base surface and remove dust.
- LACQUERED TIMBERS: Wash with a soda-based (alkaline) cleaner, rinse with copious amounts of fresh water and allow to dry. Lightly sand down the base surface using 240 grade sand paper and remove dust.
- PLYWOOD, VENEERS OR MELAMINE-COATED BOARDS: Wash with a soda-based (alkaline) cleaner, rinse with copious amounts of fresh water and allow to dry
- WAXED TIMBERS: Remove wax, rub down base surface and remove dust

### PERFORMANCE

Easy Furniture is an opaque 3-in-1 varnish:

1. It bonds, without stripping, to lacquered or veneered surfaces to be revamped.
2. It embellishes and transforms your surfaces.
3. It is stain-resistant, and protects your furniture and woodwork against everyday wear and tear.

Easy Furniture is easy to apply, and provides a highly attractive finish. Easy to maintain and is washable.

### APPLICATION

1. Stir product vigorously in order to ensure that the product is thoroughly mixed.

2. Apply a first thin coat using a brush, following the grain of the wood. Leave to dry for 4 hours.

3. Apply a second coat by the same method. Leave to dry for 12 hours. For large

vertical surfaces, application in 2 coats using a lacquer roller is recommended. For bright colours, an additional coat may be required. As this lacquer achieves optimum hardness after 20 days, the base surface should be protected (against impacts, stains, etc.) for the first 20 days.

Coverage instructions for the product should be observed - avoid applying the

lacquer too thickly or too thinly. Lacquer should be applied at an optimum temperature between 12° and 25°C in still conditions. Do not reapply to a finish

which is already drying. Clean tools in water. Clean finished surfaces using a mild detergent. Do not use abrasive sponges.



WHITE POPLIN  
SATIN

TURKISH DELIGHT  
SATIN

MARSHMALLOW  
SATIN

BLUE ICE  
SATIN

MENTHOL  
SATIN

ALMOND GREEN  
SATIN

LINEN  
SATIN

STRING  
SATIN

TAUPE  
SATIN

FELT GREY  
SATIN

ZINC  
SATIN

STONE GREY  
SATIN

BLUE STORM  
SATIN

PETROL  
SATIN

CARBON BLACK  
SATIN

LEMON ZEST  
GLOSS

SIXTIES ORANGE  
GLOSS

RED LIPSTICK  
GLOSS

ULTRA PINK  
GLOSS

ROSE WOODSTOCK  
GLOSS

ULTRAVIOLET  
GLOSS

BLUE WHIM  
GLOSS

DISCO GREEN  
GLOSS

MINT DIABOLO  
GLOSS

TROPICAL TURQUOISE  
GLOSS

#### TIPS & TRICKS



[www.v33.co.uk](http://www.v33.co.uk)  
+44 (0) 1797 367555  
Liberon Limited  
Learoyd Road, Mountfield  
Industrial Estate, New Romney,  
Kent TN28 8XU