



RENOVATION RADIATOR & HOUSEHOLD APPLIANCE

**DIRECT TO METAL
HIGH ADHESION**

SIZE: spray 400ml



HIGH PERFORMANCE FOR YOUR RENOVATION


Renovation RADIATOR & HOUSEHOLD APPLIANCE has been specially developed to easily renovate radiators and household appliances.

The paint is extremely durable and resistant on any surface (metal, PVC) to high temperatures.



- **2 in 1:** no undercoat.
- High adhesion: direct to any metals (ferrous and non ferrous) and PVC.
- HIGH RESISTANCE to heat (until 100°C).
- Does not flake: high solidity of the film towards temperature variations.
- Resistant to stains and shocks.
- Easy application: perfect finish.
- Ultra washable: easy maintenance, resistant to frequent cleaning.

COLOURCHART – satin + metallic aspect



White

Cotton

Soft grey

Loft grey

Stainless
steel
metallic

Cast iron
metallic

RENOVATION RADIATOR & HOUSEHOLD APPLIANCE

**NO UNDERCOAT -
NO STRIPPING**

Drying time:
Recoat: 15min
Fully dry: 2h

COVERAGE:
400ml = +/- 2m²

This paint has been developed for electric heaters, radiators, central heating pipes and appliances (refrigerators & dishwashers).

This paint adheres directly to ferrous (cast iron, iron) and non-ferrous (aluminum) metal surfaces.

It is NOT suitable for use on high-heat goods such as ovens, microwaves, toasters etc.



PREPARATION:

PREPARATION of the surface is ESSENTIAL.

WASH the surface with a soda-based or sugar soap (alkaline) cleaner.

- **ALUMINIUM, METAL, CAST IRON, STAINLESS STEEL** : Use a degreaser to clean the surface, then wash, rinse and allow to dry.
- **PAINTED surfaces and PVC**: wash, rinse thoroughly with water, leave to dry, then lightly sand with 240 grit sandpaper and remove dust.

APPLICATION:

Before use, be sure to turn off all radiators or other electrical appliances. Wait until the surface is cool before application. Apply in a ventilated, clean, clear and protected space.

1. Remove the safety ring located under the nozzle, shake the can until you hear the mixing ball and shake for 1 minute. Continue to shake regularly during the application.
2. Hold the aerosol upright at 15-20 cm from the surface to paint.
3. Spray by making wide and steady movements in consistent passes at equal distance from the surface. Be sure to cover the corners and edges well.
4. Avoid excessive application for a no-sag result. In the event of runs, allow to dry, sand and apply another coat.
5. After 15 minutes, apply the second coat of paint in the same way.
6. Purge the aerosol upside down by pressing the nozzle a few seconds.

V33 TIPS:

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.



DANGER - Contains ethyl acetate ; n-butyl acetate. H222 : Extremely flammable aerosol. H229: Pressurised container: may burst if heated. H319: Causes serious eye irritation. H336 : May cause drowsiness or dizziness. EUH066: Repeated exposure may cause skin dryness or cracking. P101 : If medical advice is needed, have product container or label at hand. P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 : Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. P260: Do not breathe dust/fume/gas/-mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area. P410 + P412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 : Dispose of contents/container to a waste collection center (contact the local authority).

Liberon Limited
Learoyd Road,
Mourmfield Industrial Estate,
New Romney, Kent TN28 8XU
+44 (0) 1797 367555
www.v33.co.uk

