



WOODSTAIN HIGH PROTECTION



WATER REPELLENT - WITH UV FILTERS
REINFORCED PROTECTION

Flexible with wood movement ◀
Non-drip formulation ◀
Quick dry ◀

8
YEARS
GUARANTEE



Clear
S



Light oak
M+S




Medium oak
M+S



Dark oak
M+S



Mahogany
M+S



Teck
M+S












Charcoal
M+S

Woodstain designed for :

- All exterior & interior vertical woodwork: cladding, shutters, gates, pergola, fences, windows, beams ...
- For most types of European and exotic woods, new or old (oak, softwood, larch, douglas, red cedar ...).
- Can be applied over most woodstains.

- Aspects : Matt (6) – Satin (7)
 - Sizes : 750ml – 2,5L
- Coverage : 750ml = ± 9sqm/L – 2,5L = ± 30sqm/L

 WATER REPELLENT - WITH UV FILTERS REINFORCED PROTECTION		Specially designed woodstain to protect and decorate outdoor woods exposed to bad weather conditions and UV. Its microporous formulation allows the wood to breathe.	DRYING TIME  3h  12h RECOAT FULLY DRY	
 WATER REPELLENT WITH UV FILTERS	 MICROPOROUS		TOOL CLEANING  WATER	
		TOOLS    Brush, Roller, Spray gun		

PREPARATION

The wood to be stained must be clean, dry, in good condition and not greasy. Sand the corners and edges to round them slightly.

- **RAW WOODS** : Sand with sandpaper to obtain a smooth surface and remove dust. Apply a suitable wood treatment product.
- **EXOTIC WOODS, OAK, CHESTNUT...** : Dilute the 1st coat with 15% water and apply a second non-diluted coat. On greasy woods, degrease the surface with acetone.
- **STAINED WOODS** : Brush to remove any loose or flaking finishes. Use sandpaper to obtain a smooth surface and remove dust

APPLICATION

Ideal application conditions are between 12° and 25°C, in dry, wind free weather.

- Stir the product well before and during use using a wide stirrer.
- Apply in 2 coats. For a spray application, dilute with 10% water.

V33 TIPS

- Do not apply to thermo-heated, thermo-treated or acidic woods.
- For bright colours on new or exposed woods, it may be necessary to apply a 3rd coat.
- The clear shade is recommended only for renewal on previously stained and tinted woods or only to dilute other shades.
- Results may vary according to wood species. Always test product on a small or inconspicuous area for colour, compatibility and end result.

GUARANTEE

The 8 year guarantee applies for :

- New woods or renovation of common species when product is applied according to preparation and application instructions.
- **EXPOSURE** : Only vertical surfaces. For South and South-West exposure apply 3 coats.
- The guarantee is limited to refunding of the product (presentation of the receipt and the tin) and concerns only the aspect of the paint.