



DECKING OIL

UV
RESISTANT



WATER REPELLENT - WITH UV FILTERS
REINFORCED PROTECTION

- Protects and revives ◀
- Enhanced UV filters ◀
- Compatible with most woods ◀



CLEAR

MEDIUM OAK

TEAK

V33 Decking Oil is ideal for feeding, protecting and enhancing the natural beauty of most types of timber decking.

It is perfect for reviving and restoring colour to old or new decking and is suitable for use on fences, garden sheds, gates and hot tubs etc.

The UV filters contained help reduce discolouration and fading from the sun, whilst maintaining the finish.

- Aspect : MAT
- Sizes : 2,5L– 5L
- Coverage : 2,5L = ± 20sqm/L

WATER REPELLENT - WITH UV FILTERS
REINFORCED PROTECTION



**WATER
REPELLENT
WITH UV FILTERS**



**DEPTH
PENETRATION**

Deeply impregnates the wood and protects against water, stains, grease, and UV thanks to its waterproofing power.

Microporous : allows the wood to breathe.

DRYING TIME

15 min RECOAT
24h FULLY DRY

TOOL CLEANING



TOOLS



Brush, Roller

Important:

Oil finishes bring out the natural colour of the timber. A wet surface will be an indication of the final colour. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result. Please note, this product has a milky appearance in the tin, however this disappears once dry.

PREPARATION

Ensure the surface is clean, dry and free from previous finishes and dust.
Lightly sand new wood and clean old wood with V33 Tough Deck Clean and Revive.

APPLICATION

- Apply the product in temperatures between 12°C and 25°C in dry weather.

Softwoods:

Stir well before use. Apply a generous coat of Decking Oil with a paint brush, roller or spray gun. Allow to penetrate for 15 to 30 minutes then apply the second coat without waiting for the first to dry. Continue to apply more coats of Decking Oil until the timber no longer absorbs the oil. Wipe off any oil that has not been absorbed into the timber with a lint-free cotton cloth and allow to dry for 24 to 48 hours before using the decking.

Hardwoods:

Unless the hardwood is very absorbent, best results are achieved by wiping on the oil in very thin coats with a cloth. It is essential that any oil that has not been absorbed into the timber is wiped off thoroughly with a clean lint-free cloth. For new hardwoods, it is recommended to leave the wood exposed for up to 12 months before applying any finish. This allows the grain in the wood to open and breathe and aids penetration and adhesion of the finish.

V33 TIPS

- For general maintenance clean with V33 Tough Deck Clean and Revive.
- We recommend applying 1 or 2 coats of Decking Oil at least once a year as routine maintenance. On high traffic areas re-apply 1 or 2 coats of Decking Oil as and when required.