

# RENOVATION RADIATOR & HOUSEHOLD APPLIANCE



**DIRECT TO METAL  
HIGH ADHESION**

**2 in 1:** No undercoat, direct to radiators and household appliances  
Heat resistant

## HIGH PERFORMANCE FOR YOUR RENOVATION

Renovation RADIATOR & HOUSEHOLD APPLIANCE has been specially developed to easily renovate radiators and household appliances. The paint is extremely durable and resistant on any surface (metal, PVC) to high temperatures.



- 2 in 1: no undercoat.
- High adhesion: direct to any metals (ferrous and non ferrous) and PVC.
- HIGH RESISTANCE to heat (until 100°C).
- Does not flake: high solidity of the film towards temperature variations.
- Resistant to stains and shocks.
- Easy application: perfect finish.
- Ultra washable: easy maintenance, resistant to frequent cleaning.

## COLOURCHART



White  
gloss



White  
matt



White  
satin



Soft  
grey



Gunmetal

# RENOVATION RADIATOR & HOUSEHOLD APPLIANCE

**NO UNDERCOAT  
NO STRIPPING**

Drying time  
Recoat : 6h – Fully dry: 24h  
Tools cleaning: water

COVERAGE:  
750ml = +/- 5m<sup>2</sup>

This paint has been developed for electric heaters, radiators, central heating pipes and appliances (refrigerators & dishwashers). This paint adheres directly to ferrous (cast iron, iron) and non-ferrous (aluminum) metal surfaces.

*It is NOT suitable for use on high-heat goods such as ovens, microwaves, toasters etc.*

## TOOLS:

- Paint stirrer or wide stick
- 4-5mm short pile roller
- Angled paint brush (for angles, corners & finishes)

## PREPARATION:

PREPARATION of the surface is ESSENTIAL.

WASH the surface with a soda-based or sugar soap (alkaline) cleaner.

- **ALUMINIUM, METAL, CAST IRON, STAINLESS STEEL** : Use a degreaser to clean the surface, then wash, rinse and allow to dry.
- **Aluminium, metal, cast iron, stainless steel already painted (with a solvent based paint) and PVC**: wash, rinse thoroughly with water, leave to dry, then lightly sand with 240 grit sandpaper and remove dust.

## APPLICATION:

Apply the paint at room temperature between 12 and 25°C and avoid draughts.

1. Stir the paint with a stirrer or wide stick, working around the bottom of the tin to mix it well.
2. Start by painting the angles, moldings and joints of the surface. Work on small surfaces.

Apply from one end to the other. Follow with successive cross strokes. Do not start 2nd coat while it's still drying. Leave to dry for 6h and apply a 2nd coat in the same way. A 3rd coat may be required depending on the surface and colour.

## V33 TIPS:

Wait at least 48 hours after applying the final coat before using the appliance or radiators with a gradual increase in the temperature..

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

## HEALTH & SAFETY

Contains biocidal products (preservatives): contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. EUH211 : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. P102 : Keep out of reach of children. P271 : Use only outdoors or in a well-ventilated area. P501 : Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j) : 140g/L (2010). This product contains max 29g/L VOC.



# RENOVATION RADIATOR & HOUSEHOLD APPLIANCE



**DIRECT TO METAL  
HIGH ADHESION**

**2 in 1:** No undercoat, direct to radiators and household appliances

Heat resistant



## HIGH PERFORMANCE FOR YOUR RENOVATION

Renovation RADIATOR & HOUSEHOLD APPLIANCE has been specially developed to easily renovate radiators and household appliances. The paint is extremely durable and resistant on any surface (metal, PVC) to high temperatures.



- 2 in 1: no undercoat.
- High adhesion: direct to any metals (ferrous and non ferrous) and PVC.
- HIGH RESISTANCE to heat (until 100°C).
- Does not flake: high solidity of the film towards temperature variations.
- Resistant to stains and shocks.
- Easy application: perfect finish.
- Ultra washable: easy maintenance, resistant to frequent cleaning.

## COLOURCHART



White  
gloss



White  
matt



White  
satin



Soft  
grey



Gunmetal

# RENOVATION RADIATOR & HOUSEHOLD APPLIANCE

**NO UNDERCOAT  
NO STRIPPING**

Drying time  
Recoat : 6h – Fully dry: 24h  
Tools cleaning: water

COVERAGE:  
400ml = +/- 2m<sup>2</sup>

This paint has been developed for electric heaters, radiators, central heating pipes and appliances (refrigerators & dishwashers). This paint adheres directly to ferrous (cast iron, iron) and non-ferrous (aluminum) metal surfaces.

*It is NOT suitable for use on high-heat goods such as ovens, microwaves, toasters etc.*

## PREPARATION:

PREPARATION of the surface is ESSENTIAL.

WASH the surface with a soda-based or sugar soap (alkaline) cleaner.

- **ALUMINIUM, METAL, CAST IRON, STAINLESS STEEL** : Use a degreaser to clean the surface, then wash, rinse and allow to dry.
- **PAINTED surfaces and PVC**: wash, rinse thoroughly with water, leave to dry, then lightly sand with 240 grit sandpaper and remove dust.

## APPLICATION:

Before use, be sure to turn off all radiators or other electrical appliances. Wait until the surface is cool before application. Apply in a ventilated, clean, clear and protected space.

1. Remove the safety ring located under the nozzle, shake the can until you hear the mixing ball and shake for 1 minute. Continue to shake regularly during the application. 2. Hold the aerosol upright at 15-20 cm from the surface to paint. 3. Spray by making wide and steady movements in consistent passes at equal distance from the surface. Be sure to cover the corners and edges well. 4. Avoid excessive application for a no-sag result. In the event of runs, allow to dry, sand and apply another coat. 5. After 15 minutes, apply the second coat of paint in the same way. 6. Purge the aerosol upside down by pressing the nozzle a few seconds.

## V33 TIPS:

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

## HEALTH & SAFETY

**DANGER** - Contains ethyl acetate ; n-butyl acetate, 2-methoxy-1-methylethyl acetate. EUH208 : Contains maleic anhydride. May produce an allergic reaction. EUH211 : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. H222 : Extremely flammable aerosol. H229 : Pressurised container: May burst if heated. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness. EUH066 : Repeated exposure may cause skin dryness or cracking. P101 : If medical advice is needed, have product container or label at hand. P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 : Do not spray on an open flame or other ignition source. P251 : Do not pierce or burn, even after use. P271 : Use only outdoors or in a well-ventilated area. P410 + P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF. P501 : Dispose of contents/container to a waste collection center (contact the local authority). UFI: 8P60-A076Q00V-SX8D

