



RENOVATION MULTI-SURFACE

WALLS, FLOORS, TILES, FURNITURE AND MORE

20 DIRECT TO 20 SURFACES

- ▶ **2 in 1:** no undercoat
- ▶ Resistant to water, stains and impacts



RENOVATION MULTI-SURFACE

THE SOLUTION DESIGNED TO MAKE YOUR LIFE EASIER!

Bringing old tiles back to life, refreshing wood panelling or giving furniture a makeover has never been so easy! Thanks to a 2-in-1 highly adherent formula, Renovation Multi-Surface® is the ideal multi-material solution for renovating all surfaces inside the house. It also ensures a nice result (smoothness and coverage) as well as optimal performance.



- ▶ 2 in 1: no undercoat.
- ▶ HIGH RESISTANCE to care and maintenance products: shampoos, shower gels, classic household products, anti-limescale products, diluted bleach, white vinegar...
- ▶ RESISTANT to repeated water splashing.
- ▶ Does not flake: high paint film resistance to temperature variations: hot water, cold water.
- ▶ Easy application: perfect finish.
- ▶ Ultra washable: easy maintenance.

COLOURCHART – Satin aspect



White
Matt

Porcelain
Gre

Pebble
grey

Hemp

Grey
blue

Turquin
blue

Green
khaki

Bohemian
rose

Honey
yellow

Graphite
black

RENOVATION MULTI- SURFACE

WALLS, FLOORS, TILES, FURNITURE AND MORE

**NO UNDERCOAT
NO STRIPPING**

Drying time
Recoat : 6h – Fully dry: 24h
Tools cleaning: water

COVERAGE:

75ml = +/- 1m² - 750ml = +/- 10m² - 2L = +/- 24m²

Paint designed for walls, woodwork, radiators, windows, doors, built-in and free-standing furniture, objects, worktops, floors, stairs, etc. in:

- WOOD: bare, varnished, painted or stained. For all wood types.
- WOOD DERIVATIVES: melamine, laminate, OSB and plywood.
- TILES: wall tiles, border tiles, granite and porcelain tiles.
- METAL: ferrous (iron, cast iron) and non-ferrous (aluminium, stainless steel, copper, etc.).
- GLASS.

Paint suitable for ALL rooms in the house.

Tools:

- Wide stick or paint stirrer
- 4-5mm short pile roller
- Round-edged paint brush (for angles, corners & finishes)

Preparation:

PREPARATION of the surface is ESSENTIAL. WASHING the surface with a soda-based or sugar soap (alkaline) cleaner is CRUCIAL.

- On laminate, melamine and already painted or varnished surfaces: wash, rinse thoroughly with clean water and leave to dry. Then sand lightly with a 240 grit abrasive and remove dust.
- On tiles, stainless steel, glass, etc. : wash, rinse thoroughly with clean water and leave to dry.
- On plasterboard: remove dust and then apply the appropriate undercoat for the surface.

Application:

Apply the paint at room temperature between 12 and 25°C and avoid draughts.

1. Empty the Additiv System (the sachet that is placed under the lid of the tin) into the paint. Stir the paint for 5 minutes, working around the bottom of the tin with a wide stick to mix it well.
2. Apply the paint to small areas at a time. Start by painting angles and corners with a brush. Apply the paint using criss-cross strokes and finish with even strokes in the same direction. Do not start reapplying the product while the 1st is still drying. Leave to dry for 6h and apply a 2nd coat in the same way.

Once the sachet has been added, the mixture must be used within 10 days to maintain optimal adhesion and performance. On horizontal surfaces, the paint has to be covered with the Renovation Worktop Protection.

V33 tips:

To clean your painted surfaces, use a gentle detergent and a non-abrasive sponge.

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

HEALTH & SAFETY

Contains biocidal products (preservatives): contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102 : Keep out of reach of children. P271 : Use only outdoors or in a well-ventilated area. P501 : Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j) : 140g/L (2010). This product contains max 30g/L VOC.

