



WOODSTAIN EXTREME PROTECTION



ANTI HUMIDITY BARRIER
AQUARESIST TECHNOLOGY

- High concentration of UV filters ◀
- High resistance to temperature variation ◀
- Resin reinforced for higher protection ◀

12
YEARS
GUARANTEE




Clear



Light oak



Dark oak



Mahogany



Teck

Woodstain designed for :

- All vertical external woodwork subject to severe climatic conditions (chalets, shutters, gates, windows, sub-slopes of roof, cladding ...).
- For most types of European and exotic woods, new or old (oak, softwood, larch, douglas, red cedar ...).
- Suitable on most old woodstains.

- Aspect : Satin
- Sizes : 750ml – 2,5L
- Coverage : 750ml = ± 9sqm – 2,5L = ± 30sqm



**ANTI HUMIDITY BARRIER
AQUARESIST TECHNOLOGY**



**WATER
REPELLENT
EFFECT**



**RESISTANT
to temperature
variations**

The high performance formulation ensures the waterproofing effect of the woodstain and its resistance to bad weather conditions. Thanks to its reinforced resin formula, 2 layers of EXTREME PROTECTION woodstain correspond to 3 layers of a standard woodstain.

DRYING TIME



RECOAT



FULLY DRY

TOOL CLEANING



**WHITE
SPIRIT**

TOOLS



Brush, Roller, Spray gun

PREPARATION

The wood has to be DRY and CLEAN.

- RAW OR REFURBISHED WOOD : Sand with sandpaper to obtain a smooth surface and remove dust. Apply a suitable wood treatment product.
- STAINED WOODS : Brush to remove any loose or flaking finishes. Use sandpaper to obtain a smooth surface and remove dust.
- EXOTIC WOODS, OAK, CHESTNUT... : First apply a suitable undercoat.
- GREASY WOODS : Degrease with acetone.

APPLICATION

Ideal application conditions : between 10° and 30°C, in dry weather.

We wouldn't recommend an application in strong winds or when bad weather is forecast.

- Stir the product well before and during use using a wide stirrer.
- Apply in 2 coats with a brush or a special roller for woodstain. For a spray application, dilute with 10% white spirit.

V33 TIPS

- The clear shade is recommended only for renewal on already stained and tinted woods or only to dilute other shades.
- For bright colours on new or exposed woods, it may be necessary to apply a 3rd coat.
- You are able to mix colours of Extreme Woodstain together.
- In order to preserve the remaining product, empty contents into a smaller container (no air).

GUARANTEE

The 12 year guarantee applies for :

- New woods or renovation of common species when product is applied according to preparation and application instructions.
- EXPOSURE : Only vertical surfaces. For South and South-West exposure apply 3 coats.
- The guarantee is limited to refunding of the product (presentation of the receipt and the tin) and concerns only the aspect of the paint.