



RENOVATION WORKTOP PROTECTION



REINFORCED RESISTANCE
DURABLE PROTECTION

Anti-scratch protection for worktops
Ultra-resistance to stains, grease



HIGH PERFORMANCE FOR YOUR RENOVATION

The Renovation Worktop Protection has been specially designed to durably protect high-used surfaces and materials. Thanks to the combination of specific polymers and of the Additive System, a true performance booster, it protects the Renovation paint from knocks and scratches specific to worktops.



The Renovation Worktop Protection provides long-term protection of worktops. Like an armour, the film provides durable protection against the hazards of daily life.

- **2 in 1:** no undercoat.
- Impact and scratch resistant.
- Resistant to culinary stains : hot and cold fats, vinegar, wine, ketchup, coffee and tea....
- Resistant to care and maintenance products: water, washing up liquid, multi purpose cleaner, household products, diluted bleach...
- Easy application: perfect finish.
- Ultra washable: easy maintenance.

COLOURCHART – Satin aspect



Clear

RENOVATION WORKTOP PROTECTION

**NO UNDERCOAT
NO STRIPPING**

Drying time
Recoat : 4h – Fully dry: 24h
Tools cleaning: **water**

COVERAGE:
500ml = +/- 5m

This product has been developed as a protection for horizontal surfaces (worktop, vanity top) painted with V33 Renovation Paint.

TOOLS:

- Paint stirrer or wide stick
- 4-5mm short pile roller
- Angled paint brush (for angles, corners & finishes)

PREPARATION

The Renovation Worktop Protection is essential to reinforce the resistance of horizontal surfaces repainted with the Renovation Paint.
Wait for complete drying of the paint before application of the protection.

APPLICATION

1. Empty the Additive System (the sachet that is placed under the lid of the tin) into the protection. Stir for 5 minutes to mix it well.
2. Apply the protection in 2 layers evenly, in crossed layers to ensure the performance of the protection and a neat finish. Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

Once the sachet has been added, the mixture must be used within 10 days to maintain optimal adhesion and performance.

V33 TIPS

The protected surface can be easily maintained with your usual household products.

HEALTH & SAFETY

Contains biocidal products (preservatives): contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102 : Keep out of reach of children. P271 : Use only outdoors or in a well-ventilated area. P501 : Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j) : 140g/L (2010). This product contains max 49g/L VOC.

